J-900 Flooring Plywood

Introducing the new 900mm wide lightweight ply flooring



PO Box 13647 Onehunga 1643 Auckland

Tel: 09 276 7030 Fax: 09 270 0504

www.nzwoodproducts.co.nz



Why choose plywood for your floor?

Makes a stiff and rigid floor that feels like concrete

Peace of mind through plywood's natural durability and the H3 treatment that gives protection under wet areas.

A New Zealand made product that is FSC certified and backed by the Engineered Wood Products Association of Australasia (EWPAA), providing assurance for your customers.

The benefits of using our 21mm x 900mm wide J-900 Ply Flooring

- Light One-man-panel weighing only 26kg
- Strong and stiff engineered to a minimum F8 rating
- Stability J-Ply is flat and straight
- Ideal for use under wet areas when treated H3.2
- Tongue and Grooved to remove need for intermediate nogging, minimising potential for floor to squeak and providing a better performing floor system
- Available in 2400mm, 2700mm and 3000mm lengths



End uses

- 1. Under Wet areas
- 2. Domestic Garage floors
- 3. Commercial floors
- 4. Domestic floors
- 5. Mid-section engineered floors.

21mm x 900mm x 2400mm

Span tables are listed in the New Zealand Wood Products J-Ply Roofing, Flooring and Decking Brochure

Note - Plywood is a natural product and will discolour or surface check when left exposed to the weather. If a natural clear finish is required, the ply must be protected at installation from weather and sun. It is recommended that a sample is tested for polyurethane or stain finishes.







