

NZWOOD

NEW ZEALAND WOOD PRODUCTS LIMITED

November 2013

J-900 Plywood Flooring

Introducing the new 900mm wide lightweight Plywood flooring.

Plywood makes a stiff and rigid floor that feels like concrete

Peace of mind through plywood's natural durability and the H3 treatment that gives protection under wet areas.

A New Zealand made product that is FSC certified and backed by the Engineered Wood Products Association of Australasia (EWPA), providing assurance for your



The only supplier of NZ made 3 metre plywood

Available in 21mm x 900mm x 2400mm long sheets.

End Uses for J-900 Plywood include:

- Under wet areas
- Domestic garage floors
- Commercial floors
- Domestic Floors
- Mid-section Engineered floors



IBUILTTM
Building Systems

The benefits of using our 21mm x 900mm wide J-900 Ply Flooring

- Light One-man-panel – weighing only 26kg
- Strong and stiff – engineered to a minimum F8 rating
- Stability – J-Ply is flat and straight
- Ideal for use under wet areas when treated H3.2
- Tongue and Grooved to remove need for intermediate noggings, minimising potential for floor to squeak and providing a better performing floor system
- Available in 2400mm, 2700mm and 3000mm lengths

Treatment

Structural Ply is recommended as a substrate for permanent weather barrier systems on walls, decks and roofs. Treated H3 (CCA) Ply is recommended as a substrate behind membranes, shingles and tiles. Ply with a minimum C grade face is recommended for supporting roof membranes. Rubber membrane adhesives are not compatible with LOSP H3 treatments.

Fixings

Gluing and screwing of Ply to joists improves stiffness and reduces squeaking in the finished floor.

Nailing / Screwing

Fix nails or screws at 150mm centres around panel edges and 300mm on intermediate supports. Corrosion resistant fasteners (hot dip galvanised fasteners or stainless steel) must be used when using H3 CCA treated plywood.

Span Information

Span tables for are listed in the New Zealand Wood Products J-Ply Roofing, Flooring and Decking Brochure



All products and relative statements within this document are subject to the applicable products being installed in accordance with information mentioned, and subject to any governing codes of practice. New Zealand Wood Products retains the right to change specifications without notice. Every care has been taken in preparing the information contained within this publication, however, the company cannot accept responsibility for any inaccuracies that may have arisen, and cannot accept liability for loss or damage (either direct or consequential) arising out of or in relation to use or application of the said information.

No part of this publication may be reproduced without prior written consent of New Zealand Wood Products Limited.

The information contained in this brochure relates to specific J-Ply products manufactured by Juken New Zealand Limited. The span tables cannot be applied to other plywood products however similar they appear.

NZWOOD

NEW ZEALAND WOOD PRODUCTS LIMITED

PO Box 13647, Onehunga, Auckland 1643

Tech Info Line: 0800-022-352

Phone: +64-9-276 7030

Fax: +64-9-270 0504

Email: sales@nzwoodproducts.co.nz

www.nzwoodproducts.co.nz