

GL8

H5 POSTS

by Taranakipine

GLUE LAMINATED POSTS

August 2026



Made in NZ by Taranakipine from radiata pine, these finger-jointed, glue-laminated posts are treated to hazard class H5 and planed to achieve a smooth clean visual post.

Post applications include: verandas, carports and supporting decks and roofs.

Manufactured to AS/NZS 1328:1998, AS 5068:2006
Treated in accordance to NZS3640:2003

Posts must be fully painted within 14 days of installation.
All cuts, notches and holes must be treated with a timber preservative.

The portion of the post in-ground must be sealed prior to being cast in concrete.

GL8
H5 POSTS
by Taranakipine



For full
product
information

Specification table

Post size (mm)	88x88, 112x112, 135x135, 180x180*
Post lengths (m)	2.4, 2.7, 3.0, 3.6, 4.2, 4.8, 6.0
Laminate species	Radiata pine (GL8)
Surface finish	Planed, Visual
Edge profile	Edge arrised
Preservative treatment	MCA H5
Bond Type	Structural "A" Bond
Durability	Min 50 years to meet NZBC clause B2
Manufacturing standard	AS/NZS 1328.1:1998
Construction	Top, bottom, and core are manufactured from finger-jointed lamina

*180x180 available in 3.6m and 4.2m lengths.

