

Product Description

BrightPly™ interior lining plywood is a non-structural plywood that is intended for applications where panels will be kept dry. Made from radiata pine face and back with a poplar core. Veneers are bonded using a WBP Melamine glue. These panels are extremely versatile and suitable for a wide range of interior uses such as wall & ceiling linings. Available in 9 and 12mm thicknesses, 2.4/2.7/3.0m lengths, and natural and whitewash finish.

Source of Product

BrightPly™ lining panels are manufactured in China and distributed by New Zealand Wood Products.

Whitewash panels are factory coated in New Zealand using a UV clearcoat low viscosity lacquer with a 3% whitewash tint.

NZ Distributor: New Zealand Wood Products Limited.

PO Box 76412, Manukau, Auckland 2241

www.IBuilt.co.nz

sales@IBuilt.co.nz

NZBN: 9429034720325

New Zealand Building Code Compliance

B2 Durability, B2.3.1 (a, c). Untreated timber and timber-based products are provided for in NZS 3602:2003 where the products are to be used in areas not subjected to exposure to moisture.

F2 Hazardous Building Materials, F2.3.1. untreated plywood is not considered hazardous and does not emit harmful gases.

Scope of Use

Suitable for wall and ceiling lining, and other non-building uses.

Limitations of Use

Not suitable for use in high moisture or high heat environments. Internal applications only.

These products are not subject to a warning or ban under section 26 of the Building Act 2004.

Installation

Please refer to the BrightPly™ lining installation guide available at www.ibuilt.co.nz.

Maintenance

Please refer to the BrightPly™ lining panel installation guide available at www.ibuilt.co.nz.

This document has been prepared to meet the requirements of the Building (Building Product Information Requirements) Regulations 2022.